



## Clear Gloss Inkjet (Clear/Perm/50)

### Face Stock

A 1.5 mil clear glossy polyester Ink Jet facestock. In addition to exceptional imprintability, this face material combines very good clarity with excellent heat resistance and durability.

Basis Weight:	N/A
Caliper:	0.0015 inches $\pm$ 10%
Tensile:	MD 30,000 psi CD 30,000 psi
Tear:	N/A
Stiffness:	N/A

### Adhesive Information

Adhesive is a general purpose permanent adhesive with good adhesion to many substrates, particularly corrugated. The adhesive is resistant to high temperatures from laser printers.

Type:	Emulsion Acrylic
Minimum Application Temperature:	+25°F
Service Temperature Range:	-65°F to + 200°F

### Liner Information

50# liner is a coated stock that adds to the overall stability of the total construction.

Basis Weight:	50# per ream $\pm$ 10% (500 sheets 24" x 36")
Caliper:	0.0034 inches $\pm$ 10%
Tensile:	MD 25# per inch width CD 13# per inch width
Tear:	MD 60 grams per sheet CD 75 grams per sheet

Total Construction Caliper: 0.0056 inches  $\pm$  10%

Typical Performance Data: 50# uncoated paper at room temperature on standard lab panels

Material	Loop Track	Peel Adhesion
Stainless Steel	3.7 lbs	1.7 lbs-tear
Glass	3.7 lbs	2.2 lbs-tear
Recycled Corrugated	1.9 lbs-Pulled Fiber	1.4 lbs-tear-Pulled Fiber
Polypropylene	2.9 lbs	1.3 lbs-tear
Treated HDPE	3.2 lbs	1.8 lbs-tear

### Printing/Converting

This product can be printed using most flexographic film inks and it has been die-cut and stripped at high speeds on standard web-fed presses.

### Application and Uses

This product has been designed to be compatible with most common sheet fed desktop inkjet printers. The product is suitable for a wide variety of labeling applications including but not limited to: mass customized labeling, shipping labels, address labels and compact disk labeling.

### Shelf Life

One year when stored at 72°F and 50% RH.